



REBA

USER MANUAL

POWERED BY **SRAM**

BESCHRIFTUNGEN ZUR ABBILDUNG AUF SEITE 3:

- A. Optionale Fernbedienung für PopLoc-Einstellung
- B. Floodgate
- C. Druckstufen-Einsteller
- D. Baugruppe für Druckstufenregelung
- E. Baugruppe für Zugstufenregelung

HINWEIS: DAS AUSSEHEN IHRER GABEL KANN VON DEN ZEICHNUNGEN ODER FOTOS IN DIESEM HANDBUCH ABWEICHEN.
AKTUELLE INFORMATIONEN ZU IHRER GABEL FINDEN SIE AUF UNSERER WEBSITE UNTER WWW.ROCKSHOX.COM.

LLAMADAS A LA ILUSTRACIÓN DE LA PÁGINA 3:

- A. Mando a distancia de ajuste PopLoc (opcional)
- B. Compuerta Floodgate
- C. Ajustador de la compresión
- D. Conjunto de compresión Motion Control
- E. Conjunto de rebote Motion Control

NOTA: EL ASPECTO DE SU HORQUILLA PUEDE DIFERIR DE LAS ILUSTRACIONES O FOTOGRAFÍAS DE ESTE MANUAL. PARA CONSULTAR LA INFORMACIÓN MÁS ACTUALIZADA SOBRE SU HORQUILLA, VISITE NUESTRO SITIO WEB EN WWW.ROCKSHOX.COM.

LÉGENDES DES ILLUSTRATIONS DE LA PAGE 3 :

- A. Réglage distant Poploc en option
- B. Vanne Floodgate
- C. Régleur de compression
- D. Assemblage de compression Motion Control
- E. Assemblage de rebond Motion Control

REMARQUE : L'APPARENCE DE VOTRE FOURCHE PEUT ETRE DIFFERENTE DE CELLE DES FOURCHES REPRESENTÉES SUR LES ILLUSTRATIONS/PHOTOS DE CE MANUEL. VOUS TROUVEREZ LES DERNIÈRES INFORMATIONS TECHNIQUES CONCERNANT VOTRE FOURCHE EN VISITANT NOTRE SITE INTERNET A L'ADRESSE : WWW.ROCKSHOX.COM.

RIMANDI PER LA FIGURA DI PAGINA 3:

- A. Regolazione PopLoc Remote opzionale
- B. Saracinesca
- C. Regolatore della compressione
- D. Gruppo di compressione del controllo movimento
- E. Gruppo di ritorno del controllo movimento

NOTA. L'ASPETTO EFFETTIVO DELLA FORCELLA POTRÀ ESSERE DIVERSO DALLE ILLUSTRAZIONI E DALLE FOTOGRAFIE CONTENUTE NEL PRESENTE MANUALE. PER AVERE INFORMAZIONI AGGIORNATE SULLA FORCELLA, VISITARE IL NOSTRO SITO WEB ALL'INDIRIZZO WWW.ROCKSHOX.COM.

BIJSCRIFTEN BIJ ILLUSTRATIE OP BLZ. 3:

- A. Optionele Poploc-afstelling op afstand
- B. Overloopbescherming
- C. Compressieknop
- D. Bewegingscontrole compressiemontage
- E. Bewegingscontrole terugveringsmontage

OPMERKING: UW VORK KAN ER IETS ANDERS UITZIEN DAN OP DE ILLUSTRATIES/FOTO'S IN DEZE HANDLEIDING.
BEZOEK VOOR DE MEEST RECENTE INFORMATIE OVER UW VORK ONZE WEBSITE OP WWW.ROCKSHOX.COM.

LEGENDAS DA ILUSTRACÃO DA PÁGINA 3:

- A. Regulação remota PopLoc (opcional)
- B. Regulação de Floodgate
- C. Regulador de compressão
- D. Unidade de compressão do controlo de movimento
- E. Unidade de recuperação do controlo de movimento

NOTA: O ASPECTO DA FORQUETA PODE NÃO SER EXACTAMENTE O DAS ILUSTRAÇÕES OU FOTOGRAFIAS DESTES MANUAIS.
PARA INFORMAÇÕES TÉCNICAS ACTUALIZADAS ACERCA DA FORQUETA, VISITE O WEBSITE WWW.ROCKSHOX.COM.

F. Zugstufen-Einsteller

- G. Negativ-Luftventil
- H. Dual Air-Kolben
- I. Air U-Turn-Einsteller
- J. Positiv-Luftventil

F. Ajustador del rebote

- G. Válvula de la cámara de aire negativa
- H. Pistón Dual Air
- I. Conjunto del Air U-Turn
- J. Válvula de la cámara de aire positiva

F. Molette de réglage du rebond

- G. Valve à air négative
- H. Piston Dual Air
- I. Assemblage pneumatique Air U-Turn
- J. Valve à air positive

F. Regolatore del ritorno


- G. Valvola dell'aria negativa
- H. Pistone aria doppio
- I. Gruppo U-Turn ad aria
- J. Valvola dell'aria positiva

F. Terugveringsknop

- G. Negatief luchtventiel
- H. Dual Air zuiger
- I. Montage Air U-Turn
- J. Positief luchtventiel

F. Regulador de recuperação

- G. Válvula de ar negativo
- H. Pistão de Dual Air
- I. Unidade de U-Turn pneumático
- J. Válvula de ar positivo



NOTE: YOUR FORK'S APPEARANCE MAY VARY FROM THE ILLUSTRATIONS/PHOTOS IN THIS MANUAL.

FOR THE LATEST INFORMATION ABOUT YOUR FORK VISIT OUR WEBSITE AT WWW.ROCKSHOX.COM.

Congratulations! You have the best in suspension components on your bicycle! This manual contains important information about the safe operation and maintenance of your fork. To ensure that your RockShox fork performs properly, we recommend that you have your fork installed by a qualified bicycle mechanic. We also urge you to follow our recommendations to help make your riding experience more enjoyable and trouble-free.

IMPORTANT Consumer Safety Information

1. The fork on your bicycle is designed for use by a single rider, on mountain trails, and similar off-road conditions.
2. Before riding the bicycle, be sure the brakes are properly installed and adjusted. Use your brakes carefully and learn your brakes' characteristics by practicing your braking technique in non-emergency circumstances. Hard braking or improper use of the front brake can cause you to fall. If the brakes are out of adjustment, improperly installed or are not used properly, the rider could suffer serious and/or fatal injuries.
3. Your fork may fail in certain circumstances, including, but not limited to, any condition that causes a loss of oil; collision or other activity bending or breaking the fork's components or parts; and extended periods of non-use. Fork failure may not be visible. Do not ride the bicycle if you notice bent or broken fork parts, loss of oil, sounds of excessive topping out, or other indications of a possible fork failure, such as loss of shock absorbing properties. Instead, take your bike to a qualified dealer for inspection and repair. In the event of a fork failure, damage to the bicycle or personal injury may result.
4. Always use genuine RockShox parts. Use of aftermarket replacement parts voids the warranty and could cause structural failure to the shock. Structural failure could result in loss of control of the bicycle with possible serious and/or fatal injuries.
5. Use extreme caution not to tilt the bicycle to either side when mounting the bicycle to a carrier by the fork drop-outs (front wheel removed). The fork legs may suffer structural damage if the bicycle is tilted while the drop-outs are in the carrier. Make sure the fork is securely fastened down with a quick release. Make sure the rear wheel is fastened down when using ANY bike carrier that secures the fork's drop-outs. Not securing the rear can allow the bike's mass to side-load the drop-outs, causing them to break or crack. If the bicycle tilts or falls out of its carrier, do not ride the bicycle until the fork is properly examined for possible damage. Return the fork to your dealer for inspection or call RockShox if there is any question of possible damage (See the International Distributor List). A fork leg or drop-out failure could result in loss of control of the bicycle with possible serious and/or fatal injuries.
6. **Forks designed for use with 'v'-style brakes:** only mount cantilever-type brakes to the existing brake posts. Forks with hangerless style braces are only designed for 'V'-style or hydraulic cantilever brakes. Do not use any cantilever brake other than those intended by the brake manufacturer to work with a hangerless brace. Do not route the front brake cable and/or cable housing through the stem or any other mounts or cable stops. Do not use a front brake cable leverage device mounted to the brace. **Forks designed for use with disc-style brakes:** follow the brake manufacturer's installation instruction for proper installation and mounting of the brake caliper.
7. Observe all owner's manual instructions for care and service of this product.

ROCKSHOX FORKS ARE DESIGNED FOR COMPETITIVE OFF-ROAD RIDING AND DO NOT COME WITH THE PROPER REFLECTORS FOR ON-ROAD USE. YOUR DEALER SHOULD INSTALL PROPER REFLECTORS TO MEET THE CONSUMER PRODUCT SAFETY COMMISSION'S (CPSC) REQUIREMENTS FOR BICYCLE STANDARDS IF THE FORK IS GOING TO BE USED ON PUBLIC ROADS AT ANY TIME.

FORK INSTALLATION

It is extremely important that your RockShox fork is installed correctly by a qualified bicycle mechanic. Improperly installed forks are extremely **dangerous** and can result in **severe and/or fatal injuries**.

1. Remove the existing fork from the bicycle and the crown race from the fork. Measure the length of the fork steerer tube against the length of the RockShox steerer tube. The RockShox steerer tube may need cutting to the proper length. Make sure there is sufficient length to clamp the stem (refer to the stem manufacturer's instructions).

⚠ WARNING

DO NOT ADD THREADS TO ROCKSHOX THREADLESS STEERERS. THE STEERER TUBE CROWN ASSEMBLY IS A ONE-TIME PRESS FIT. REPLACEMENT OF THE ASSEMBLY MUST BE DONE TO CHANGE THE LENGTH, DIAMETER OR HEADSET TYPE (THREADED OR THREADLESS).

DO NOT REMOVE OR REPLACE THE STEERER TUBE. THIS COULD RESULT IN THE LOSS OF CONTROL OF THE BICYCLE WITH POSSIBLE SERIOUS AND/OR FATAL INJURIES.

2. Install the headset crown race (29.9mm for 1 1/8" steerers) firmly against the top of the fork crown. Install the fork assembly on the bike. Adjust the headset until you feel no play or drag.
3. Install the brakes according to the manufacturer's instructions and adjust brake pads properly. Use the fork only with disc style brakes mounted through the provided mounting holes.
4. **Forks designed for standard quick releases:** adjust the front wheel quick release to clear the dropout's counter bore. The quick release nut must be tightened after the wheel is properly seated into the dropout's counter bore. Make sure four or more threads are engaged in the quick release nut when it is closed. Orient the quick release lever in front of and parallel to the lower tube in the locked position. **Forks designed for a thru-axle (not available for all forks):** follow the installation instructions that follow for the Maxle Quick Release system.
5. Keep in mind tire clearance as you choose tires. **Maximum size is 2.4" wide or 696 mm diameter installed.** Be sure to check this diameter whenever you change tires. To do this, remove air pressure and compress the fork completely to make sure at least 5 mm of clearance exists between the top of the tire and the bottom of the crown. Exceeding maximum tire size will cause the tire to jam against the crown when the fork is fully compressed.

POPLOC REMOTE INSTALLATION

The PopLoc Remote Lockout lever allows the rider to control the movement of their suspension fork without removing their hands from the handlebars.

If needed, remove the grip, brake lever, and shifter from the left side (rider's perspective) of the handlebar. If you are unfamiliar with the removal of these items, please consult the manufacturer's instructions.

1. Slide the Poploc onto the handlebar.
2. Re-install the shifter, brake lever, and grip on the handlebars. If you are unfamiliar with the installation of these items, please consult the manufacturer's instructions. Always adhere to the recommended torque specifications for these items.
3. Position the PopLoc as desired on the handlebar and tighten the clamp bolt to 20 in-lb (2.25 Nm)
4. Forks with PopLoc Adjust: Turn the blue compression adjustment dial counterclockwise until it stops.
5. Press the release button on the PopLoc.
6. Install the cable in the PopLoc.
7. Install the cable into the housing.

8. Feed the cable and housing into the cable stop on the fork crown.
9. Gently pull on the cable and align it with the groove in the rotating cam of the Motion Control damper.
10. Tighten the cable fixing bolt on the rotating cam to 8 in-lb (9 Nm)

PERFORMANCE TUNING

RockShox forks can be tuned for your particular weight, riding style and terrain.

Air Spring Tuning

With independently adjustable positive (top) and negative (bottom) air chambers, the air spring system of your Reba fork can be easily tuned for your weight and riding style. Use the following instructions as a starting point. If further fine tuning is desired, follow the hints at the end of this section.

STEP 1 - SELECTING POSITIVE AIR PRESSURE

Positive air pressure determines the amount of force required to compress your fork. More positive air pressure will result in less suspension sag and higher bottom out forces. Less positive air pressure will result in more suspension sag and lower bottom out forces.

Using the chart below as a guideline, inflate the positive air chamber to the desired pressure,

NOTE: AIR U-TURN PRESSURE SHOULD BE SET AT 115MM OF TRAVEL.

Rider Weight	Pressure Air U-Turn	Pressure Dual Air
< 140 (63kg)	80-115 psi	70-100 psi
140 - 160 (63-72 kg)	115-130 psi	100-115 psi
160 - 180 (72-81 kg)	130-145 psi	115-130 psi
180 - 200 (81-90 kg)	145-160 psi	130-145 psi
>220 (99 kg)	180 psi	160 psi

STEP 2 - SELECTING NEGATIVE AIR PRESSURE

Negative air pressure effects the amount of force required to initiate suspension travel. Negative air pressure works with bump input AGAINST the force of the positive air chamber. More negative air pressure results in a suspension set-up that is more active, especially to small bump input. Less negative air pressure results in a suspension set-up does not move or "bob" under rider input or small bumps. Using the chart below as a guideline, inflate the negative air chamber to the desired pressure.

Rider Weight	Air U-Turn (Pressures):		Dual Air (Pressures):	
	More Active	Less Active	More Active	Less Active
< 140 (63kg)	80-115 psi	50-70 psi	70-100 psi	40-60 psi
140-160 (63-72kg)	115-130 psi	70-80 psi	100-115 psi	60-70 psi
160-180 (72-81kg)	130-145 psi	80-90 psi	115-130 psi	70-80 psi
180-200 (81-90 kg)	145-160 psi	90-100 psi	130-145 psi	80-90 psi
>220 (99 kg)	180 psi	110 psi	160 psi	100 psi

Motion Control Damping System

IMPORTANT NOTE: WHEN STORING A BICYCLE OR FORK UPSIDE-DOWN OR ON ITS SIDE, OIL SEALED IN THE UPPER TUBE CAN COLLECT ABOVE THE MOTION CONTROL DAMPER ASSEMBLY. UPON RETURNING THE BICYCLE/FORK TO A NORMAL RIDING POSITION, INITIAL PERFORMANCE OF THE MOTION CONTROL SYSTEM MAY BE LESS THAN OPTIMAL. TO QUICKLY RETURN THE FORK TO PROPER PERFORMANCE, RETURN THE FORK TO 'OPEN' POSITION AND CYCLE THE FORK THROUGH ITS TRAVEL 10-20 TIMES. FOR INFORMATION ON RETURNING YOUR FORK TO 'OPEN' POSITION, KEEP READING!

The Motion Control Damping system allows riders to quickly adjust the feel and performance of their suspension to match riding conditions without requiring pumps or tools. This system provides for wide-ranging control of compression and rebound damping as well as 'Lock' threshold sensitivity.

Proper setup of the Motion Control Damping system provides a range of options for efficient yet comfortable performance. The instructions below describe setup and operation for both crown and remote activated forks.

'OPEN' COMPRESSION (FIG. 1)

In the 'Open' position, the Motion Control Damping system allows for maximum compliance and fork movement. The 'Open' position provides ultimate control and comfort on even the roughest terrain.

To return your fork to the 'Open' position:

- For forks with the crown-mounted blue compression adjuster, rotate the adjuster fully counterclockwise.
- For PopLoc equipped forks, press the 'Unlock' release button on the remote (as indicated by the open padlock icon on the button).




Fig. 1

'Lock' COMPRESSION (FIG. 2)

In the 'Lock' position, the Motion Control system allows for a small amount of controlled fork movement. This movement enables the front tire to track the terrain without deflecting off obstacles, allowing for better traction and steering control when compared to a complete lockout system. To activate the 'Lock', turn the crown-mounted blue compression adjuster full clockwise or press forward on the PopLoc Remote lever located on the handlebar.




Fig. 2

FLOODGATE ADJUSTMENT (FIG. 3)

All forks with Motion Control Damping allow for fine-tuning of the 'Lock' setting. The rider can choose the point at which the 'Lock' setting can 'blow-off' and become active to force inputs such as bumps or rocks. This adjustment is made using the Floodgate. Depending upon fork model, the Floodgate is adjusted either internally (requires a 2.5mm hex wrench) or externally with the gold 'Gate' adjuster.

For crown mounted adjusters, hold the adjuster in the 'Lock' position while adjusting the internal Floodgate.

NOTE: THE FLOODGATE IS INTENDED TO ADJUST THRESHOLD OF 'LOCK' BLOW-OFF IN THE 'LOCK' MODE ONLY. WHEN PERFORMING FLOODGATE ADJUSTMENTS, ENSURE THAT THE MOTION CONTROL SYSTEM IS ADJUSTED TO 'LOCK.'

Under 'Lock', the maximum Floodgate setting results in a fork with minimal movement while the minimum Floodgate setting results in increased fork movement.

NOTE: FOR MAXIMUM FORK SENSITIVITY AND MOVEMENT, RETURN THE FORK TO THE 'OPEN' POSITION.

Floodgate settings should be used to adjust suspension compliance to medium sized bumps and resistance to rider induced suspension movement (referred to as "bob") in the 'Lock' mode. When properly tuned, the Motion Control System will resist "bob," but provide controlled suspension action in rough or aggressive terrain.

Under 'Lock', heavier riders may find better performance with maximum Floodgate settings, while lighter riders may find minimum Floodgate settings work best. Experiment with higher or lower Floodgate settings while on the trail to optimize your fork for your riding style and performance preferences.

Use the charts below to establish an initial Floodgate setting.

All settings from Maximum Floodgate (or full clockwise)

EXTERNAL FLOODGATE (RACE AND TEAM MODELS)

Rider weight lb (kg)	Full Turns Counterclockwise
< 120 (< 54 kg)	4 - 5
120 - 150 (54 - 68 kg)	3 - 4
150 - 180 (68 - 82 kg)	2 - 3
180 - 210 (82 - 95 kg)	1 - 2
210 < (95 kg <)	0 - 1

INTERNAL FLOODGATE (SL MODEL)

Rider weight lb (kg)	Full Turns Counterclockwise
< 120 (< 54 kg)	2.0 +
120 - 150 (54 - 68 kg)	1.5 - 2.0
150 - 180 (68 - 82 kg)	1.0 - 1.5
180 - 210 (82 - 95 kg)	0.5 - 1.0
210 < (95 kg <)	0.0 - 0.5

Floodgate Adjustment

('Lock' blowoff force when the fork is in 'Lock' mode)




Fig. 3

TIP: THE REBOUND ADJUSTER ON THE BOTTOM RIGHT FORK LEG CAN BE USED TO ADJUST INTERNAL FLOODGATE MODELS. GENTLY PULL DOWNWARD ON THE REBOUND ADJUSTER FOR REMOVAL. REMOVE THE GOLD 'GATE' DUST CAP AND INSERT THE 2.5MM HEX END OF THE REBOUND ADJUSTER INTO THE FLOODGATE. **DON'T FORGET TO RE-INSTALL THE ADJUSTER AFTER USE!**

COMPRESSION ADJUSTMENT (FIG. 4)

Some fork models also feature adjustable compression damping. Increased compression decreases fork movement in the 'Open' position. Compression adjustment can be used to help combat brake dive and "squatting" under hard cornering.

For crown activated forks, compression damping increases to 'Lock' as the crown-mounted actuator rotates 90 degrees clockwise. Position the actuator anywhere within the range from 'Open' to 'Lock' to suit the desired level of compression damping.

Forks equipped with the PopLoc Adjust provide compression damping adjustment for the 'Open' position. Turning the blue adjuster on the PopLoc adjust clockwise increases compression damping for the 'Open' position. The PopLoc lever features gradients to help illustrate the current level of compression. Eight complete turns of adjustment are provided.

TIP: ADJUSTING COMPRESSION ON FORKS EQUIPPED WITH POPLOC ADJUST IS BEST DONE WITH THE FORK IN 'LOCK' POSITION.

NOTE: THE COMPRESSION SETTING DOES NOT ADVERSELY EFFECT YOUR FORK'S PERFORMANCE OVER HIGH SPEED IMPACTS.




Fig. 4

External Rebound Adjustment

Rebound damping controls the speed at which a fork returns to its full extension following compression. Located at the bottom of the right fork leg is the rebound adjuster knob. Turning the adjuster in the direction indicated by the "rabbit" on the rebound speed decal decreases rebound damping, causing the fork to return to full extension faster. Turning the adjuster in the direction indicated by the "turtle" increases rebound damping, slowing the return of the fork to full extension.

Excessive rebound damping will cause the fork to "pack up" over successive bumps, reducing travel and causing the fork to bottom out. Set your fork to rebound as fast as possible without "topping out" or kicking back. This allows your fork to follow the contours of the trail, maximizing stability, traction and control.

FURTHER TUNING HINTS

Setting Sag

RockShox forks are designed to sag when you are sitting on your bike. Sag is compression of the fork caused by the rider's weight. Proper sag allows the front wheel to follow the contour of the terrain as you ride. Sag is adjusted by increasing or decreasing the positive air pressure of your fork. Increasing the pressure in your positive chambers will decrease sag. Decreasing the pressure in your positive air chamber will increase sag.

To measure sag, use the travel indicator on the upper tube of the fork and ensure it is flush against the wiper seal. For Air U-Turn, ensure travel is set at the maximum (see "Changing Travel"). Sit on the bike with normal riding apparel. Step off the bike, and measure the distance between the wiper seal and the travel indicator. This distance is your sag. The sag should be approximately 20 percent of maximum travel. Example: For 115mm maximum travel, $0.20 \times 115\text{mm} = 23\text{mm}$ sag distance.

Changing Travel

DUAL AIR VERSION

To change the travel of your fork for 85mm, 100mm or 115mm you must perform a full service on your fork. To obtain service information or instructions, visit our website at www.rockshox.com or contact your local RockShox dealer or distributor.

AIR U-TURN VERSION

To change the travel of your fork anywhere between 85mm and 115mm, turn the Air U-Turn knob (top left knob on fork). Clockwise rotation reduces the travel of the fork. Counterclockwise rotation increases the travel of the fork. The new travel setting can be seen by looking at the travel marking that remains exposed on the left upper tube when not sitting on the bike. The reduced travel setting will have slightly lower bottom out force, therefore additional compression damping may be desired.

NOTE: ENSURE THE FORK IS COMPRESSED ONCE AFTER SITTING FOR MORE THAN A DAY AND IN 'OPEN' POSITION BEFORE TRAVEL ADJUSTMENT.

MAINTENANCE

To maintain the high performance, safety, and long life of your fork, periodic maintenance is required. If you ride in extreme conditions, maintenance should be performed more frequently.

* WE RECOMMEND THIS SERVICE BE PERFORMED BY A QUALIFIED BICYCLE MECHANIC. TO OBTAIN SERVICE INFORMATION OR INSTRUCTIONS, VISIT OUR WEBSITE AT WWW.ROCKSHOX.COM OR CONTACT YOUR LOCAL ROCKSHOX DEALER OR DISTRIBUTOR.

Torque Tightening Values

Top Caps	65 in-lb
Brake Posts	80 in-lb
Shaft Bolts	60 in-lb
PopLoc Remote handlebar clamp bolt	20 in-lb
PopLoc Remote cable fixing bolt	8 in-lb

SERVICE INTERVALS	GPS Metro	Judy TT/C	Judy XC / Pilot C	Judy SL	Pilot XC/SL
Clean dirt and debris from upper tubes	E	E	E	E	E
Inspect upper tubes for scratches	E	E	E	E	E
Lubricate dust seals/tubes	10	10	10	10	10
Check top caps, brake posts and shaft bolts for proper torque	25	25	25	25	25
Check air pressure	*	*	*	*	E
Remove lowers, clean/inspect bushings and change oil bath	*	*	50	50	50
Change oil in Pure system	*	*	*	*	*
Change oil in Motion Control System	*	*	*	*	100
Clean and lubricate Air U-Turn/Dual Air/Air Assist assembly	*	*	*	*	50
Clean and lubricate coil spring or coil U-Turn spring assembly	100	100	100	100	*
Clean and lubricate PopLoc cable and housing	*	*	*	*	50
	Reba SL, Race & Team	SID Race, SL & World Cup	Pike SL, Race & Team	Boxxer Ride, Race, Team & World Cup	
Clean dirt and debris from upper tubes	E	E	E	E	
Inspect upper tubes for scratches	E	E	E	E	
Lubricate dust seals/tubes	10	10	10	E	
Check top caps, brake posts and shaft bolts for proper torque	25	25	25	25	
Check air pressure	E	E	*	*	
Remove lowers, clean/inspect bushings and change oil bath	50	50	50	25	
Change oil in Pure system	*	100	*	*	
Change oil in Motion Control System	100	*	100	*	
Clean and lubricate Air U-Turn/Dual Air/Air Assist assembly	50	50	*	*	
Clean and lubricate coil spring or coil U-Turn spring assembly	*	*	100	*	
Clean and lubricate PopLoc cable and housing	50	50	50	*	

Notes:

E = Every ride

Numeric values represent hours of riding time.

Increase service intervals based on rider weight, aggressive riding style/conditions, inclement weather and racing

SRAM CORPORATION WARRANTY**Extent of Limited Warranty**

SRAM warrants its products to be free from defects in materials or workmanship for a period of two years after original purchase. This warranty only applies to the original owner and is not transferable. Claims under this warranty must be made through the retailer where the bicycle or the SRAM component was purchased. Original proof of purchase is required.

Local law

This warranty statement gives the customer specific legal rights. The customer may also have other rights which vary from state to state (USA), from province to province (Canada), and from country to country elsewhere in the world.

To the extent that this warranty statement is inconsistent with the local law, this warranty shall be deemed modified to be consistent with such law, under such local law, certain disclaimers and limitations of this warranty statement may apply to the customer. For example, some states in the United States of America, as well as some governments outside of the United States (including provinces in Canada) may:

- Preclude the disclaimers and limitations of this warranty statement from limiting the statutory rights of the consumer (e.g. United Kingdom).
- Otherwise restrict the ability of a manufacturer to enforce such disclaimers or limitations.

Limitations of Liability

To the extent allowed by local law, except for the obligations specifically set forth in this warranty statement, In no event Shall SRAM or its third party supplies be liable for direct, indirect, special, incidental, or consequential damages.

Limitations of Warranty

- This warranty does not apply to products that have not been incorrectly installed and/or adjusted according to the respective SRAM technical installation manual. The SRAM installation manuals can be found online at www.sram.com or www.rockshox.com.
- This warranty does not apply to damage to the product caused by a crash, impact, abuse of the product, non-compliance with manufacturers specifications of usage or any other circumstances in which the product has been subjected to forces or loads beyond its design.
- This warranty does not apply when the product has been modified.
- This warranty does not apply when the serial number or production code has been deliberately altered, defaced or removed.
- This warranty does not apply to normal wear and tear. Wear and tear parts are subject to damage as a result of normal use, failure to service according to SRAM recommendations and/or riding or installation in conditions or applications other than recommended.

WEAR AND TEAR PARTS ARE IDENTIFIED AS:

- Dust seals
- Air sealing o-rings
- Rubber moving parts.
- Rear shock mounting hardware and main seals
- Stripped threads/bolts (aluminium, titanium, magnesium or steel)
- Brake pads
- Sprockets
- Shifter and brake cables (inner and outer)
- Shifter grips
- Disc brake rotors
- Bushings
- Glide rings
- Foam rings
- Upper tubes (stanchions)
- Brake sleeves
- Chains
- Cassettes
- Handlebar grips
- Jockey wheels
- Tools

- This warranty shall not cover damages caused by the use of parts of different manufacturers.
- This warranty shall not cover damages caused by the use of parts that are not compatible, suitable and/or authorised by SRAM for use with SRAM components.